



## **COMFORT**





TECHNICAL INFORMATION			
Felt	Grızzled - White	150 Gr – 500 Gr	
Shock Pad	Cross-linked Polyethylene	8 – 20 MM	30 – 50 Density
Synthetic Grass	18 MM - 20 MM - 24 MM - 25 MM - 30 MM - 35 MM - 40 MM COMFORT		
Base Cloth	165 GR PP BASE CLOTH		
Backing	1.035- 1.100 GR LATEX		
Yarn	6.000 /6 DTEX	%100 PE Monofilament	
Knot Number	12.750 - 27.690 ADET		
Yarn Weight	471 GR - 1.520 GR		
Total Weight	1.596 GR - 2.645 GR		
Helmetin Cloth	450 Gr Tarpaulin		
Adhesive	21 + 4 Kg Two-component Polyurethane Adhesive		
Silica Sand	0.2 - 1.0 Mm Dried And Kiln-dried Round Silica Sand (10-14 Kg)		
Optional	Sılıca Sand, Shock Pad		

INSTALLATION METHOD		
Infrustructure	May Be Concrete, Asphalt And Gravel. The Gravel Surface Must Be Levelled.	
Felt	Protective And Sand Holding Felt Is Wetted And Layed Under The Grass Carpet.	
Synthetic Grass	The Grass Carpet Rolls That Fit The Project Are Opened Side By Side, And The Joints Are Cut To Match.	
Helmetin Cloth	Helmettin Cloth Is Used To Combine Pieces Of Grass Carpet.	
Adhesive	Well-mixed Two Component Adhesive Is Applied To The Helmetin Cloth, Placing It Between Two Pieces Of Grass Carpet And Making Sure That The Grass Carpet Edge Meets Well With The Adhesive.	

COLORS		
Grass Carpet Light Green, Dark Green, Mixed Green		

KEY BENEFITS		
Grass Carpet	Meets Fıfa Standards, Performance Close To Natural Grass, Ideal For Countries With Cold And Hot Climate.	
Shock Pad	Preferred For Shock Absorption Performance.	
Sılıca Sand	It Has The Ability To Drain 100% Of The Water, Making Grass Carpet Fibers Stand Upright.	





PACKAGING TYPES		
Felt	It Is Wrapped As Roll Of 2m Width.	
Shock Pad	It Is Wrapped As Roll Of 1.5m Width.	
Grass Carpet	It Is Wrapped As Roll In 4m Width.	
Helmetin Cloth	It Is Wrapped As Roll.	
Adhesive	Buckets 0f 21+4 Kg.	
Silica Sand	Sacks 0f 50 Kg / 1000 Kg.	
Other	In Various Ways, Its Palette Is Sacks And Free Goods.	

STORAGE CONDITIONS		
Glue And Its Derivatives In Unopened Packagings, It Can Be Stored For 12 Months From +5 To +30 Degrees.		
Other Materials	In Unopened Packagings, It Can Be Stored For 24 Months From +0 To +40 Degrees.	

MANUFACTURING AND INSTALLATION TIME			
Infrustructure	Preperation: 1 Day	Construction: 2-7 Days	Cannot Be Applied Simultaneously
Shock Pad	Manufacturing: 10 Days	Installation: 1-2 Days	Cannot Be Applied Simultaneously
Grass Carpet	Manufacturing: 10 Days	Installation: 2-7 Days	Cannot Be Applied Simultaneously
Silica Sand	Manufacturing: 7Days	Installation: 1-5 Days	Cannot Be Applied Simultaneously
Granule	Supply: 7 Days	Installation: 1-2 Days	Cannot Be Applied Simultaneously

WARRANTY			
Grass Carpet Uv Warranty	3-5 Years	5% Tolerance	
Grass Carpet Yarn Breaking	3-5 Years	10% Tolerance	
Sılıca Sand	3-5 Years	15% Tolerance	
Sbr Granule	3-5 Years	10% Tolerance	
Application Warrant	2 Years	In Case Of Maintenance Agreement (5 Years)	

## **COMFORT**















Merkez/Head Office: Metro 34 Plaza No: 23/100, İOSB Bedrettin Dalan Bulvarı Başakşehir - İstanbul / TÜRKİYE

Fabrika/Factory: Velimeşe OSB 93. Sokak No:101 Çorlu - Tekirdağ / TÜRKİYE