



MULTI SPORTS LSR





TECHNICAL INFORMATION			
Synthetic Grass	15 MM – 18 MM – 20 MM – 22 MM– 24 MM – 26 MM – 28 MM LSR FIBRILE		
Backing	165 GR PP BACKING		
Latex	700 GR- 850 GR LATEX		
Yarn	5.000 DTEX	%100 PE Fibrillated	
Number of Stiches	22.365 – 26.625 Units		
Yarn Weight	521 Gr- 757 Gr		
Carpet Weight	1.450 Gr – 1.670 Gr		
Joint Tape	450 GR Tarpaulin		
Adhesive	21 + 4 KG Double Components Polyurethane Adhesive		
Silica Sand	0.2 – 1.0 MM Dried and Baked Round Silica Sand (15 – 25 Kg)		

INSTALLATION METHOD		
Subbase	Concrete or asphalt surface should be preferred. There must be a two-sided or one-sided surface slope.	
Synthetic Grass	The grass rolls are laid side by side according to the project, and the joints are cut and combined.	
Field Line	The field lines are original white-yellow grass carpets cut into 8-12 cm width and laid on the grass field.	
Joint Tape	Joint Tape is used to connect grass carpet pieces together.	
Adhesive	Thoroughly mixed two-component adhesive is applied to the joint tape and placed between two grass carpet pieces, ensuring that the edges of the grass carpets are in good contact with the adhesive.	
Silica Sand	Silica sand is applied equally to grass carpet with special equipment and machines. Level correction is then performed.	

COLORS		
Grass Carpet	Light Green, Dark Green, Mixed Green	
Grass Carpet Line	White, Yellow, Red	
Outside the Line	Green, Red	





ADVANTAGES		
Grass Carpet With its similarity to natural grass, ideal for cold and hot countries.		
Silica Sand	It has the ability to drain the water 100%, it helps to stable grass carpet by its weight.	
Ball Bounce	Tennis and basketball games can be played. The ball can jump due to the sand infill.	

PRODUCT PACKAGING		
Grass Carpet	It is rolled up in 4 M width.	
Joint Tape	It comes in roll.	
Adhesive	21+4 KG buckets.	
Silica Sand	50Kg/1000 Kg bags.	
Other	Variously, pallets, sacks and at large products.	

PRODUCT STORAGE		
Adhesive and Its Derivative	Unopened packages can be stored between +5 and +30 degrees for 12 months.	
Other Materials	Unopened packages can be stored between 0 and +40 degrees for 24 months.	

DELIVERY AND INSTALLATION PERIODS			
Grass Carpet	Production: 10 Days	Installation: 2-7 Days	Can not work simultaneously
Shock Pad	Production: 7 Days	Installation: 1-5 Days	Can not work simultaneously

WARRANTY PERIODS		
Grass Carpet UV Warranty	3-5 YEARS	% 5 Tolerance
Grass Carper Yarn Breakage	3-5 YEARS	% 10 Tolerance
Silica Sand	3-5 YEARS	% 15 Tolerance
Installation Warranty	2 YEARS	5 years with maintenance contract

MULTI SPORTS LSR

EXAMPLES OF APPLICATIONS















Merkez/Head Office: Metro 34 Plaza No: 23/100, İOSB Bedrettin Dalan Bulvarı Başakşehir - İstanbul / TÜRKİYE

Fabrika/Factory: Velimeşe OSB 93. Sokak No:101 Çorlu - Tekirdağ / TÜRKİYE