



PREMIUM



TECHNICAL INFORMATION			
Felt	Grızzled - White	150 Gr – 500 Gr	
Shock Pad	Cross-linked Polyethylene	8 – 20 MM	30 – 50 Density
Synthetic Grass	40 MM - 50 MM - 55 MM - 60 MM PREMIUM		
Base Cloth	165 GR - 220 GR PP BASE CLOTH		
Backing	1.230 - 1.370 GR LATEX		
Yarn	13.200/6 DTEX	%100 Pe Monofilament	V Shape - Spined
Knot Number	7.650 8.288 PCS		
Yarn Weight	981 GR - 1.397 GR		
Total Weight	2.174 GR - 2.904 GR		
Helmetin Cloth	450 Gr Tarpaulin		
Adhesive	21 + 4 Kg Two-component Polyurethane Adhesive		
Sılıca Sand	0.2 - 1.0 Mm Dried And Kiln-dried Round Silica Sand (10-14 Kg)		
Granule	1 - 3.5 Mm Black Dust-free Sbr Rubber Granule (5 - 9 Kg)		
Optional	Shock Pad, Gray Or Green Epdm Filling		

INSTALLATION METHOD			
Infrustructure	Infrustructure Gravel Ground Will Be Corrected In Accordance With The Football Field Special Code.		
Felt	Protective And Sand Holding Felt Is Wetted And Layed Under The Grass Carpet.		
Shockpad	It May Be Used Optionally, Rolls Are Layed And Combined With Special Tape.		
Synthetic Grass	Helmettin Cloth Is Used To Combine Pieces Of Grass Carpet.		
Game Line			
Helmetin Cloth			
Adhesive	Well-mixed Two Component Adhesive Is Applied To The Helmetin Cloth, Placing It Between Two Pieces Of Grass Carpet And Making Sure That The Grass Carpet Edge Meets Well With The Adhesive.		
Silica Sand	Silica Sand Is Implemented Equally In The Grass Carpet With The Help Of Specialized Equipment And Machines. Then Level Correction Is Performed.		
Granule	Granule After Silica Sand, Rubber Granules Are Applied Equally With The Help Of Special Equipment And Machines. The Field Will Be Ready To Play By Finishing The Final Level Correction.		

COLORS		
Grass Carpet Light Green, Dark Green, Mixed Green		
Grass Carpet Line White, Yellow, Red		
Out Of Line	Green, Red	





	KEY BENEFITS		
Grass Carpet Meets Fifa Standards, Performance Close To Natural Grass, Ideal For Countries With Cold And Hot Clin			
Shock Pad	Preferred For Shock Absorption Performance.		
Silica Sand It Has The Ability To Drain 100% Of The Water, Making Grass Carpet Fibers Stand Upright.			
Granule	It Provides The Nearest Performance To Natural Grass In Shock Absorption, Ball Rolling And Ball Bouncing.		

PACKAGING TYPES			
Felt	Felt It Is Wrapped As Roll Of 2m Width.		
Shock Pad It Is Wrapped As Roll Of 1.5m Width.			
Grass Carpet It Is Wrapped As Roll In 4m Width.			
Helmetin Cloth	Helmetin Cloth It Is Wrapped In Round Roll.		
Adhesive	Adhesive In Buckets Of 21+4 Kg.		
Silica Sand	Silica Sand Sacks 0f 50 Kg / 1000 Kg.		
Granule	Granule Sacks 0f 50 Kg / 1000 Kg		
Other In Various Ways, Its Palette Is Sacks And Free Goods.			

		STORAGE CONDITIONS		
		In Unopened Packagings, It Can Be Stored For 12 Months From +5 To +30 Degrees.		
		In Unopened Packagings, It Can Be Stored For 24 Months From +0 To +40 Degrees.		

MANUFACTURING AND INSTALLATION TIME			
Infrustructure	Preperation: 1 Day	Construction: 2-7 Days	Cannot Be Applied Simultaneously
Shock Pad	Manufacturing: 10 Days	Installation: 1-2 Days	Cannot Be Applied Simultaneously
Grass Carpet	Manufacturing: 10 Days	Installation: 2-7 Days	Cannot Be Applied Simultaneously
Silica Sand	Manufacturing: 10 Days	Installation: 1-5 Days	Cannot Be Applied Simultaneously
Granule	Supply: 7 Days	Installation: 1-2 Days	Cannot Be Applied Simultaneously

WARRANTY			
Grass Carpet Uv Warranty	5-7 YEARS	5% Tolerance	
Grass Carpet Yarn Breaking	5-7 YEARS	10% Tolerance	
Sılıca Sand	5-7 YEARS	15% Tolerance	
Sbr Granule	5-7 YEARS	10% Tolerance	
Application Warranty	2 YEARS	In Case Of Maintenance Agreement (5 Years)	

PREMIUM















Merkez/Head Office: Metro 34 Plaza No: 23/100, İOSB Bedrettin Dalan Bulvarı Başakşehir - İstanbul / TÜRKİYE

Fabrika/Factory: Velimeşe OSB 93. Sokak No:101 Çorlu - Tekirdağ / TÜRKİYE