

#### wwweavengrassecom

## APPLICATION AREAS

Professional Fields, Practice Fields, Rugby Fields, and Mini Football Fields.

### SYSTEM DESCRIPTION

Integral Super C is one of the most common products preferred in professional football fields. It confirms to international standards.

### **FEATURES**

With its performance similarity to natural grass, Super V can maintain its performance for many years due to its special polyethylene material. In addition, due to its UV resistance, the color quality is maintained and the player and the spectators enjoy the natural grass pleasure for many years.

# **SUPER C GRASS**

krách Adalah Bria podobne Kelevil Veden vel dzedelik visikeh zározáte. Adalah Brah Aba se kelete sektekbéle, A



**Outside the Line** 

Green, Red



TECHNICAL INFORMATION				
Felt	Mealy – White	150 Gr – 500 Gr		
Shock Pad	Cross-Linked Polyethylene	8 – 20 MM	30 – 50 Density	
Synthetic Grass	40 MM – 50 MM – 55 MM – 60 MM SUPER C			
Backing	165 GR – 220 GR PP BACKING			
Latex	1.200 GR – 1.370 GR LATEX			
Yarn	12.000/6 DTEX %100 PE Monofilament C Shape - Spine		C Shape - Spine	
Number of Stiches	8.288 – 8.925 Units			
Yarn Weight	960 Gr - 1.469 Gr			
Carpet Weight	2.137 Gr – 2.839 Gr			
Joint Tape	450 GR Tarpaulin			
Adhesive	21 + 4 KG Double Components Polyurethane Adhesive			
Silica Sand	0.2 – 1.0 MM Dried and Baked Round Silica Sand (20- 35 Kg)			
Granule	1 - 3.5 MM Black SBR Rubber Granule without Dust (5-9 Kg)			
Optional	Shock Pad, Grey or Green Epdm Infill			
	APPLICATI	ON METHOD		
Subbase	The stone chips surface will be leveled in a complete anolar form according to the special code of the football field.			
Felt	Protective and sand-holding material under the grass carpet is spread by wetting it.			
Shock Pad	It is optional, the rolls are laid and combined with special tape.			
Synthetic Grass	The grass rolls are laid side by side according to the project, and the joints are cut and combined.			
Field Line	The field lines are original white-yellow grass carpets cut into 8-12 cm width and laid on the grass field.			
Joint Tape	Joint Tape is used to connect grass carpet pieces together.			
Adhesive	Thoroughly mixed two-component adhesive is applied to the joint tape and placed between two grass carpet pieces, ensuring that the edges of the grass carpets are in good contact with the adhesive.			
Silica Sand	Silica sand is applied equally to grass carpet with special equipment and machines. Level correction is then performed.			
Granule	The rubber granules are then applied equally with special equipment and machines after silica sand, and then the final level correction is made to make the field ready to play game.			
COLORS				
Grass Carpet	Light Green, Dark Green, Mixed Green			
Grass Carpet Line	White, Yellow, Red			





ADVANTAGES			
Grass Carpet	With its similarity to natural grass in FIFA standards, ideal for cold and hot countries		
Shock Pad	It is an important product due to its shock absorption feature.		
Silica Sand	It has the ability to drain the water 100%, it helps to stable grass carpet by its weight.		
Granule	It provides the closest performance to natural grass in shock absorption, ball rolling and ball bouncing in ball jumping provide the closest performance.		

PRODUCT PACKAGING		
Felt	It is rolled up in 2 M width.	
Shock Pad	It is rolled up in 1.5 M width.	
Grass Carpet	It is rolled up in 4 M width.	
Joint Tape	It comes in roll.	
Adhesive	21+4 KG buckets.	
Silica Sand	50Kg/1000 Kg bags.	
Granule	50 Kg/1000 Kg bags.	
Other	Variously, pallets, sacks and at large products.	

PRODUCT STORAGE		
Adhesive and Its Derivative Unopened packages can be stored between +5 and +30 degrees for 12 months.		
Other Materials	Unopened packages can be stored between 0 and +40 degrees for 24 months.	

PRODUCTION AND INSTALLATION PERIODS				
Subbase	Preparation: 1 Day	Construction: 2-7 Days	Cannot Work Simultaneously	
Shock Pad	Production: 10 Days	Installation: 1-2 Days	Cannot Work Simultaneously	
Grass Carpet	Production: 10 Days	Installation: 1-2 Days	Cannot Work Simultaneously	
Silica Sand	Production: 10 Days	Installation: 1-2 Days	Cannot Work Simultaneously	
Granule	Supplying: 7 Days	Installation: 1-2 Days	Cannot Work Simultaneously	

WARRANTY PERIODS				
Grass Carpet UV Warranty	5-7 YEARS	% 5 Tolerance		
Grass Carper Yarn Breakage	5-7 YEARS	% 10 Tolerance		
Silica Sand	5-7 YEARS	% 15 Tolerance		
SBR Granule	5-7 YEARS	% 10 Tolerance		
Installation Warranty	2 YEARS	5 years with maintenance contract		

ni ka di kiri di karan Ardakiri di

# SUPER C GRASS EXAMPLES OF APPLICATIONS







+90 212 678 13 13 +90 212 678 13 13 info@avengrass.com
Merkez/Head Office: Metro 34 Plaza No: 23/100, İOSB Bedrettin Dalan Bulvarı Başakşehir - İstanbul / TÜRKİYE
Fabrika/Factory: Velimeşe OSB 93. Sokak No:101 Çorlu - Tekirdağ / TÜRKİYE